

4. ボーリング方式・二重ケーシング式
(1) SH工法

平成 19年度

品 名	種別・規格	摘 要	質量(kg)	単位	価 格		
					積算資料	建設物価	平 均
推進機	SHM 600		6,900	基	35,700,000	35,700,000	35,700,000
	SHM 800		10,300	"	37,800,000	37,800,000	37,800,000
	SH 46		5,500	"	32,400,000	32,400,000	32,400,000
バケット	0.5m3			台	198,000	198,000	198,000
偏芯先導管	400			本	133,000	133,000	133,000
	450			"	137,000	137,000	137,000
	500			"	142,000	142,000	142,000
	550			"	162,000	162,000	162,000
	600			"	170,000	170,000	170,000
	700			"	198,000	198,000	198,000
	800			"	227,000	227,000	227,000
内管 (ケーシング・ロッド)	400	L = 3 m		本	241,000	241,000	241,000
	450			"	251,000	251,000	251,000
	500			"	257,000	257,000	257,000
	550			"	277,000	277,000	277,000
	600			"	282,000	282,000	282,000
	700			"	308,000	308,000	308,000
	800			"	338,000	338,000	338,000
内管 (ケーシング・ロッド)	400	L = 1 m		本	230,000	230,000	230,000
	500			"	241,000	241,000	241,000
	600			"	262,000	262,000	262,000
先導体 (刃先本体)	400			本	1,330,000	1,330,000	1,330,000
	450			"	1,420,000	1,420,000	1,420,000
	500			"	1,450,000	1,450,000	1,450,000
	550			"	1,680,000	1,680,000	1,680,000
	600			"	1,740,000	1,740,000	1,740,000
	700			"	2,050,000	2,050,000	2,050,000
	800			"	2,300,000	2,300,000	2,300,000
切削ビット	400			本	286,000	286,000	286,000
	450			"	289,000	289,000	289,000
	500			"	302,000	302,000	302,000
	550			"	335,000	335,000	335,000
	600			"	352,000	352,000	352,000
	700			"	453,000	453,000	453,000
	800			"	504,000	504,000	504,000