

**SGP 基本仕様**

呼径	外径mm	重量kg/m	Uボルト	L寸
15A	21.7	1.305	w5/16	31
20A	27.2	1.685	w5/16	37
25A	34	2.431	w5/16	44
32A	42.7	3.384	w5/16	52
40A	48.6	3.893	w3/8	62
50A	60.5	5.314	w3/8	74
65A	76.3	7.468	w3/8	88
80A	89.1	8.794	w3/8	101
100A	114.3	12.19	w3/8	126
125A	139.8	15.02	w1/2	154
150A	165.2	19.75	w1/2	182
200A	216.3	30.11	w1/2	232

**JIS B 2301 10Kねじ継手**

呼径	めねじmm	L(C-E)	45° (C-E)	角Ni
15A	11	27	21	42
20A	13	32	25	47
25A	15	38	29	52
32A	17	46	34	56
40A	18	48	37	60
50A	20	57	42	66
65A	23	69	49	73
80A	25	78	54	81
100A	28	97	65	92
125A	30	113	74	104
150A	33	132	82	116

**20Kねじ継手 HB 消防安全センター認定品**

呼径	めねじmm	L(C-E)	45° (C-E)	角Ni
15A		32	25.5	
20A	16.3	36.5	28.5	50
25A	19.1	41.5	33.5	65
32A		49.5	38	65
40A	22.1	54	43	65
50A	25.4	63.5	51	75
65A	29.7	74.5	57	100
80A	31.2	86	63.5	83
100A	34	105	74.5	102
125A	38	125	84	116